KB-801S



Smart Card USB Keyboard for PC, Low Profile

With the latest technology of IC card reader, the KB-801S, stylish & low profile smart card USB keyboard is designed to meet your security needs in different applications such as in E-Banking, E-Payment, Transportation, E-Government. Being PS/SC and CCID complaint device, the KB-801S is easy to install and use a sit is specifically designed to be integrated in a PC environment. Its drivers are compatible with Windows OS and Linux.

KEYBOARD SPECIFICATION			
Key Number	109/ 110 keys (US/ EU)	Scissor-type Key Switch	
Key Switch	Scissor-type Key switch	Key Cap Key Cap Scissor Stems Rubber Dome	
Switch Life Cycle	5 millions life time rubber dome		
Key Force / Travel Distance	55 +/- 7gm; 2.1 +/- 0.2mm		
LED Indicators	CapLock, NumLock, Smart Card Reader		
Input Power / Interface	5VDC, 100mA; USB 1.1 version		
Special Function Keys	Play, Mute, Volume +, Volume -, Sleep	·	

SMART CARD READER SPECIFICATION		
Standard	ISO7816 Class A, B and C (5V, 3V, 1.8V), T=0 and T=1	
Protocols	T=0, T=1.2=wire; SLE 4432/42 (S=10), 3-wire; SLE441828 (S=9), 12C (S=8)	
Read & Write Speed	344 Kbps / up to 4MHz	
Card Type Support	5V, 3V and 1.8V smart card ISO 7816 Class A, AB and C	
API Support	PCSC, CCID	
PC/SC Driver Compliance	Windows 98/ME/2000/XP (32bit), 2003 Server Win, Window NT Windows CE 5.0/	
	CE.NT, Windows XP 64bit, Windows Vista (32 bit/64 bit), Windows 7, Linux	
Reliability	100K card insertions	

OTHERS		
Environment	Operating Tem.	0 ~ 50 degrees Celsius (10 ~ 95% RH, 25 degree Celsius)
	Storage Tem.	-10 ~ 65 degree Celsius (5% ~ 90% RH, 25 degree Celsius)
Physical	Dimension	434.2 (L) x 115.3 (W) x 25 (H) mm, including rubber feet
	Weight	0.6 kgs (N.W.); 0.75 kgs (G.W.)



Side Insertion

* Features and specification are subject to change without notice.



DIGIMORE ELECTRONICS CO., LTD 10 Fl., No. 61, Yan-Ping S. Rd., Taipei 100, Taiwan TEL: +886 2 2311 3299 FAX: +886 2 2311 3375 Email: info@capacity-keyboard.com http://www.capacity-keyboard.com